

# **GFT RIDER**



**CATÁLOGO CAMIÓN**

**2023**

# GF118 NOM



Size	PR	Load Index	Speed Symble	Load Capacity Kgs		Inflation Pressure Kpa	Standar rim	Overall Diameter mm	Section Width mm	Tread Depth mm	Tread Width mm
				Single	Dual						
11R22.5	16PR	146/143	L	3000	2725	830	8.25	1054	279	16.5	214
11R24.5	16PR	149/146	L	3250	3000	830	8.25	1104	279	16.5	214
9.00R20	16PR	144/142	K	2800	2650	900	7.00	1019	259	15.5	195
10.00R20	18PR	149/146	K	3250	3000	930	7.50	1054	278	16.5	214
11.00R20	18PR	152/149	K	3550	3250	930	8.00	1085	293	17	223
12.00R20	20PR	156/153	J	4000	3650	900	8.50	1125	315	17.5	240



# NOM TS282

Size	PR	Load Index	Speed Symble	Load Capacity Kgs		Inflation Pressure Kpa	Standar rim	Overall Diameter mm	Section Width mm	Tread Depth mm	Tread Width mm
				Single	Dual						
11R22.5	16PR	146/143	M	3000	2725	830	8.25	1054	279	15	220
11R22.5	18PR	149/146	M	3250	3000	930	8.25	1054	279	15	220
11R24.5	16PR	149/146	M	3250	3000	830	8.25	1104	279	15	220
295/80R22.5	18PR	152/149	M	3550	3250	900	9.00	1044	298	17	245
315/80R22.5	20PR	157/154	M	4125	3750	900	9.00	1076	312	15.5	250
315/80R22.5	22PR	164/160	L	5000	4500	900	9.00	1076	312	15.5	250

# GF909 NOM



Size	PR	Load Index	Speed Symble	Load Capacity Kgs		Inflation Pressure Kpa	Standar rim	Overall Diameter mm	Section Width mm	Tread Depth mm	Tread Width mm
				Single	Dual						
11R22.5	16PR	146/143	L	3000	2725	830	8.25	1065	279	20.5	215
11R24.5	16PR	149/146	L	3250	3000	830	8.25	1116	279	20.5	215

# GF766 NOM



Size	PR	Load Index	Speed Symble	Load Capacity Kgs		Inflation Pressure Kpa	Standar rim	Overall Diameter mm	Section Width mm	Tread Depth mm	Tread Width mm
				Single	Dual						
11R22.5	16PR	146/143	M	3000	2725	830	8.25	1054	279	14.5	220
11R24.5	16PR	149/146	M	3250	3000	830	8.25	1104	279	14.5	220
295/75R22.5	16PR	146/143	M	3000	2725	830	9	1014	298	14.5	220



# **NOM** **TD275**

Size	PR	Load Index	Speed Symble	Load Capacity Kgs		Inflation Pressure Kpa	Standar rim	Overall Diameter mm	Section Width mm	Tread Depth mm	Tread Width mm
				Single	Dual						
11R22.5	16PR	146/143	L	3000	2725	830	8.25	1065	279	22.5	224
11R22.5	18PR	149/146	L	3250	3000	930	8.25	1065	279	22.5	224
11R24.5	16PR	149/146	L	3250	3000	830	8.25	1116	279	22.5	224



# ***GFT RIDER***

**CATÁLOGO CAMIÓN**