

**GODDARD
TIRES**

GODDARD



GODDARD TIRES
PRODUCT CATALOGUE

**MAKING EVERY TIRE
WITH DEDICATION**

GODDARD



GODDARD

Contents

CRADEC GC688	01
LIBERUD GL267	03
LIBERUD GL268	05
SOPHYS GS329	07
SOPHYS GS328	09
TRANSFORCE 100	11
TRANSFORCE 168	13
TRANSFORCE 300	15
TRANSFORCE 568	17
TRANSFORCE 768	19





A/T

CRADEC GC688

POWERFUL WITH PASSION, EASY STEERING

- ◎The streamlined wide main ditch design creates a large drainage space between the tire and the road surface, enabling the tire to throw a large amount of water concentrated in the middle to the back, effectively improving the drainage performance and ensuring the wetland handling.
- ◎Shoulder pattern block bridge design, enhance the rigidity of the shoulder pattern block, ensure the ground pressure distribution is more uniform, effectively prevent partial wear.
- ◎Tread pattern block small furrow design, enhance comfort, and use its sharp edge to scrape water film, improve the traction of wetland and snow.
- ◎The 688 is an all-road SUV tire, the preferred tire for all-road cross-country enthusiasts. Paved road surface or mountain road, dirt road, snow and ice road and other non-paved road, show excellent grip and sports performance.

SIZE	LOAD INDEX	SPEED RANGE	STANDARD RIM	SECTION WIDTH (MM)	OVERALL DIAMETER (MM)	MAX LAOD SINGLE		MAX PRESSURE		TREAD DEPTH (MM)
						KG	LBS	KPa	PSI	
215/75R15	100	S	6J	216	703	800	1764	350	50	9
LT235/75R15	110/107	S	6 1/2J	235	733	1060	2335	450	65	9
235/70R16	106	T	7J	240	736	950	2094	350	51	9
245/70R16	111XL	T	7J	248	750	1090	2403	340	50	9
265/70R16	112	T	8J	272	778	1120	2469	350	51	9
265/65R17	112	H	8J	272	776	1120	2469	300	44	9



- ◎Specially reinforced structural design, good load performance and durability.
- ◎Three zigzag longitudinal grooves and tread formula design, improve tire wear resistance, prolong the service life of the tire.
- ◎Closed shoulder design, effectively reduce tire noise, improve tire wear resistance and control performance.

SIZE	LOAD INDEX	SPEED RANGE	STANDARD RIM	SECTION WIDTH (MM)	OVERALL DIAMETER (MM)	MAX LOAD SINGLE		MAX PRESSURE		TREAD DEPTH (MM)
						KG	LBS	KPa	PSI	
175/70R14LT	95/93	S	5J	177	602	690	1521	375	54	9



LT TIRE

LIBERUD GL267

PRACTICAL AND EXTRAORDINARY, LEAD WEALTH



- ◎The design of high density polyester cord and high strength steel wire belting layer ensure the super-strong load performance.
- ◎The design of three continuous tortuous longitudinal main drains improves the drainage performance of the tire, safer drive in rainy days.
- ◎Two center continuous bars and pattern block design on the shoulder ensure the stability and handling performance".

SIZE	LOAD INDEX	SPEED RANGE	STANDARD RIM	SECTION WIDTH (MM)	OVERALL DIAMETER (MM)	MAX LAOD SINGLE		MAX PRESSURE		TREAD DEPTH (MM)
						KG	LBS	KPa	PSI	
165R13C	94/93	R	4.50B	165	594	670	1477	450	65	9
185R14C	102/100	Q	5 1/2J	189	652	850	1875	450	65	9
185R15C	103/102	Q	5 1/2J	189	677	875	1930	450	65	9
195/70R15C	104/102	Q	6J	201	655	900	1984	450	65	9
195R15C	106/104	R	5 1/2J	196	693	950	2094	450	65	9



XL

LIBERUD GL268

BEARING HEAVY TRUST,HASSLE-FREE ALL THE TIME





SNOW TIRE

SOPHYS GS329

- ◎ Snow pattern designed for driving in snow and ice.
- ◎ The design of multi-steel sheet and large pattern effectively improve the anti-skid ability.
- ◎ Special snow tread rubber keep elasticity at low temperature, ensure grip.

SIZE	LOAD INDEX	SPEED RANGE	STANDARD RIM	SECTION WIDTH (MM)	OVERALL DIAMETER (MM)	MAX LAOD SINGLE		MAX PRESSURE		TREAD DEPTH (MM)
						KG	LBS	KPa	PSI	
215/55R16	93	T	7J	226	642	650	1433	300	44	8.8
215/50R17	95XL	H	7J	226	648	690	1521	340	50	8.8
225/50R17	94	T	7J	233	658	670	1477	300	44	8.8
245/70R17	110	T	7J	248	776	1060	2337	300	44	9.4
225/55R18	98	T	7J	233	705	750	1653	300	44	9
235/55R18	100	T	7.1/2J	245	715	800	1764	300	44	9
235/60R18	103	T	7J	240	739	875	1929	300	44	9
235/50R19	99	H	7.1/2J	245	719	775	1079	300	44	8.8
225/55R19	99	H	7J	233	731	775	1079	300	44	8.8
235/55R19	105XL	H	7.1/2J	245	741	925	2039	340	50	8.8



SNOW TIRE

SOPHYS GS328

- ◎ Snow pattern designed for driving in snow and ice.
- ◎ Multi-steel, multi-angular snow pattern design ensure high grip on snow and ice roads.
- ◎ Deep and densely distributed grooves and steel sheets help soften tread and shorten braking distance on snow and ice surfaces.
- ◎ Special tread glue keep elasticity at low temperatures, ensuring grip.

SIZE	LOAD INDEX	SPEED RANGE	STANDARD RIM	SECTION WIDTH (MM)	OVERALL DIAMETER (MM)	MAX LAOD SINGLE		MAX PRESSURE		TREAD DEPTH (MM)
						KG	LBS	KPa	PSI	
155/65R13	73	T	41/2J	157	532	365	805	350	51	7.5
155/70R13	75	T	4.50B	157	548	387	850	350	51	7.5
165/70R13	79	T	5.00B	170	562	437	963	350	51	8
175/70R13	82	T	5.00B	177	576	475	1047	350	51	7.5
175/65R14	82	T	5J	177	584	475	1047	350	51	9
175/70R14	84	T	5J	177	602	500	1102	300	44	9
185/60R14	82	T	51/2J	189	578	475	1047	350	51	9
185/65R14	86	T	5 1/2J	189	596	530	1168	350	51	8.7
185/70R14	88	T	5 1/2J	189	616	560	1235	300	44	8.3
185/60R15	84	T	5 1/2J	189	603	500	1102	350	51	8.7
195/60R15	88	T	6J	201	615	560	1235	350	51	8.7
185/65R15	88	T	5 1/2J	189	621	560	1235	300	44	9
195/55R15	85	T	6J	201	595	515	1135	300	44	8.3
195/65R15	91	T	6J	201	635	615	1356	350	51	7.9
205/60R15	91	T	6J	209	627	615	1355	350	51	9
205/65R15	94	T	6J	209	647	670	1477	350	51	8.7
205/55R16	91	H	61/2J	214	632	615	1356	350	51	8.8
205/60R16	92	T	6J	209	652	630	1389	350	51	9
215/60R16	95	T	6 1/2J	221	664	690	1521	350	51	9
225/60R16	98	T	6 1/2J	228	676	750	1652	350	51	9
205/50R17	89	H	6 1/2J	214	638	580	1279	350	51	8.7
225/45R17	91	H	7 1/2J	225	634	615	1356	350	51	8.7
215/55R17	94	T	7J	226	668	670	1477	300	44	8.7
225/55R17	97	T	7J	233	680	730	1609	300	44	8.7
215/60R17	96	T	6 1/2J	221	690	710	1565	300	44	8.7
225/60R17	99	T	6 1/2J	228	702	775	1709	300	44	8.7
225/65R17	102	T	6 1/2J	228	724	850	1874	300	44	8.7
215/55R18	95	T	7J	226	693	690	1521	300	44	8.7
225/60R18	100	T	6 1/2J	228	727	800	1764	300	44	8.7
245/55R19	103	T	7 1/2J	253	753	875	1929	300	44	8.7
215/45R17	87	H	7J	213	626	545	1201	350	51	8



COMFORTABLE TIRE

TRANSFORCE 100

FOLLOW YOUR HEART, THE ULTIMATE EXPERIENCE

- ◎ Crown center orientation continuous rib, ensure the straight line stability of the tire.
- ◎ Reasonable pattern spacing arrangement and special pattern block design , super quiet performance and dry wetland gripping force.
- ◎ The shoulder anti-wear strip stabilizes the shoulder profile and ensures the stability of the tire shoulder during high-speed turning.
- ◎ Horizontal streamlined grooves have excellent drainage performance and wet road grip. Better handling, more stable at high speeds.

SIZE	LOAD INDEX	SPEED RANGE	STANDARD RIM	SECTION WIDTH (MM)	OVERALL DIAMETER (MM)	MAX LOAD SINGLE		MAX PRESSURE		TREAD DEPTH (MM)
						KG	LBS	KPa	PSI	
155/65R13	73	T	4.50B	157	532	560	1235	300	44	7.2
155/70R13	75	T	4.50B	157	548	615	1356	300	44	7.2
165/60R14	75	T	5J	170	554	690	1521	300	44	7.2
165/65R13	77	T	5.00B	170	544	615	1356	300	44	7.2
165/70R13	79	T	5.00B	170	562	560	1235	300	44	7.2
165/70R14	81	T	5.00B	170	588	500	1102	300	44	7.2
175/60R13	77	H	5.00B	177	540	437	963	300	44	7.2
175/65R14	82	H	5J	177	584	670	1477	300	44	7.5
175/70R13	82	T	5.00B	177	576	500	1102	300	44	7.5
175/70R14	84	H	5.00B	177	602	475	1047	300	44	7.2
185/55R15	82	V	6J	194	585	530	1168	300	44	7.2
185/60R14	82	H	51/2J	189	578	630	1389	300	44	7.2
185/60R15	84	H	51/2J	189	603	750	1653	300	44	7.2
185/60R16	86	H	51/2J	189	628	530	1165	250	36	7.2
185/65R14	86	H	51/2J	189	596	475	1047	300	44	7.2
185/65R15	88	T	51/2J	189	621	530	1168	300	44	7.2
185/70R14	88	H	51/2J	189	616	387	853	300	44	7.2
195/50R15	82	H	6J	201	577	412	908	300	44	8
195/55R15	85	V	6J	201	595	475	1047	300	44	7.2
195/60R14	86	H	6J	201	590	475	1047	300	44	7.2
195/60R15	88	V	6J	201	615	475	1047	300	44	7.2
195/60R16	89	H	6J	201	640	412	908	300	44	7.2
195/65R15	91	V	6J	201	635	387	853	300	44	7.2
195/70R14	91	H	6J	201	630	615	1356	300	44	8
205/55R16	91	V	61/2J	214	632	730	1609	340	50	7.2
205/60R16	92	H	6J	209	652	690	1521	300	44	8
205/65R15	94	V	6J	209	647	580	1279	300	44	7.2
215/55R16	97XL	V	7J	226	642	750	1653	340	50	7.2
215/60R16	95	H	61/2J	221	664	500	1102	340	50	7.2
215/65R16	98	H	61/2J	221	686	615	1356	340	50	8
225/60R16	98	V	61/2J	228	676	730	1609	340	50	7.2
225/55R16	95	V	7J	233	654	670	1477	340	50	7.2



SNOW TIRE

TRANSFORCE 168

- ©Comfortable and quiet pattern design, using short pitch, large number of irregular arrangement, reduce tire noise.
- ©Spiral groove design helps drainage and excellent wet grip.
- ©Special composite design reduces heat generation from the shoulder and improves grip performance in all road conditions.

SIZE	LOAD INDEX	SPEED RANGE	STANDARD RIM	SECTION WIDTH (MM)	OVERALL DIAMETER (MM)	MAX LOAD SINGLE		MAX PRESSURE		TREAD DEPTH (MM)
						KG	LBS	KPa	PSI	
205/60R16	92	H	6J	209	652	630	1389	300	44	7.2
205/55R16	91	V	6 1/2J	214	632	615	1356	300	44	7.2
215/60R16	95	H	6 1/2J	221	664	690	1521	300	44	7.2
195/65R15	91	V	6J	201	635	615	1356	300	44	7.2
175/70R14	84	H	5.00B	177	602	500	1102	300	44	7.2
205/50R17	89	V	6 1/2J	214	638	580	1279	300	44	7
215/50R17	91	W	7J	226	648	615	1356	300	44	7
185/70R14	88	T	5 1/2J	189	616	560	1235	300	44	7



UHP TIRE

TRANSFORCE 300

LEADING THE TIMES, NAVIGATE THE FUTURE

- ◎The asymmetrical pattern gives superior handling on the outside, handle all kinds of roads.
- ◎Four optimum widths of gutters ensure the tyre's drainage performance, maximising the tyre's resistance to wet slip.
- ◎The wide pattern block on the tire shoulder and the pattern block stability design ensure the stability of the vehicle and bring driver precise driving feeling when changes lanes or turns at high speed.
- ◎Crown spiral groove design provides excellent drainage performance and wet road grip while maximizing high speed performance and more stable handling.

SIZE	LOAD INDEX	SPEED RANGE	STANDARD RIM	SECTION WIDTH (MM)	OVERALL DIAMETER (MM)	MAX LAOD SINGLE		MAX PRESSURE		TREAD DEPTH (MM)
						KG	LBS	KPa	PSI	
215/40ZR18	89XL	W	71/2J	218	629	750	1653	300	44	8
205/40ZR17	84XL	W	7 1/2J	212	596	365	805	300	44	8
205/45ZR17	88XL	W	7J	206	616	560	1235	300	44	8
205/50ZR17	93XL	W	6 1/2J	214	638	515	1135	300	44	8
195/55R16	87	V	6J	201	620	462	1019	300	44	7.2
215/45ZR17	91XL	W	7 J	213	626	750	1653	340	50	8
215/45ZR18	93XL	W	7J	213	651	825	1819	340	50	8
215/50ZR17	95XL	W	7J	226	648	580	1279	340	50	8
215/55ZR17	98XL	W	7J	226	668	650	1433	340	50	8
225/40ZR18	92XL	W	8J	230	637	650	1433	340	50	8
225/45ZR17	94XL	W	7 1/2J	225	634	750	1653	340	50	8
225/45ZR18	95XL	W	7 1/2J	225	659	875	1929	340	50	8
225/50ZR17	98XL	W	7J	233	658	800	1764	340	50	8
225/55ZR17	101XL	W	7J	233	680	560	1235	340	50	8
235/40ZR18	95XL	W	8 1/2J	241	645	775	1709	340	50	7.8
235/45ZR17	97XL	W	8J	236	644	690	1521	340	50	8
235/45ZR18	98XL	W	8J	236	669	800	1764	340	50	8
235/50ZR17	100XL	W	7 1/2J	245	668	630	1389	340	50	8
235/55ZR17	103XL	W	7 1/2J	245	690	690	1521	340	50	8
245/40ZR18	97XL	W	8 1/2J	248	653	730	1609	340	50	7.2
245/45ZR17	99XL	W	8J	243	652	690	1521	340	50	7.2
245/45ZR18	100XL	W	8J	243	677	545	1200	300	44	7.2



Urban SUV

TRANSFORCE 568

ACCOMPANY ALL THE WAY, NAVIGATE SPLENDID

©Powerful luxury SUV oriented ultra-high speed tires with four wide longitudinal drainage gutters and wide lateral drainage gutters improve the drainage performance, good traction and braking performance on wet roads.

©Wide driving surface, high groove separation, excellent performance, quiet design and variable sound frequency block bring quiet ride experience. unique tire side protection layer have puncture resistance and damage prevention performance.

SIZE	LOAD INDEX	SPEED RANGE	STANDARD RIM	SECTION WIDTH (MM)	OVERALL DIAMETER (MM)	MAX LAOD SINGLE		MAX PRESSURE		TREAD DEPTH (MM)
						KG	LBS	KPa	PSI	
215/70R16	100	T	6 ½J	221	708	800	1764	300	44	7.8
225/70R16	103	T	6 1/2J	228	722	875	1929	300	44	7.8
215/60R17	96	H	6 ½J	221	690	710	1565	300	44	7.8
225/60R17	99	V	6 1/2J	228	702	775	1709	300	44	7.8
225/65R17	102	V	6 ½J	228	724	850	1874	300	44	7.8
235/65R17	108XL	H	7J	240	738	1000	2205	340	50	7.8
265/65R17	112	H	8J	272	776	1120	2465	350	51	7.8
215/55R18	95	V	7J	226	693	690	1521	300	44	7.8
235/55R18	100	V	7 ½J	245	715	800	1764	300	44	7.8
235/60R18	107XL	H	7J	240	739	975	2150	290	42	7.8
235/65R18	106	H	7J	240	763	950	2094	300	44	7.8
225/55R19	99	V	7J	233	731	775	1709	300	44	7.8
235/55R19	105 XL	V	7 1/2J	245	741	925	2039	340	50	7.8
245/55ZR19	103	W	7 1/2J	253	753	875	1929	300	44	7.8



UHP TIRE

TRANSFORCE 768

- ©Asymmetric pattern design, effectively improve the control of turning.
- ©The continuous crown layer fastens the edge area of the belt under the condition of high speed driving, maintain the lasting endurance and high speed of driving.
- ©Rim protectors help prevent damage beyond the wheel mark by contact with the curb.

SIZE	LOAD INDEX	SPEED RANGE	STANDARD RIM	SECTION WIDTH (MM)	OVERALL DIAMETER (MM)	MAX LAOD SINGLE		MAX PRESSURE		TREAD DEPTH (MM)
						KG	LBS	KPa	PSI	
225/55ZR18	98	W	7J	233	705	750	1653	300	44	8
255/50ZR19	103	W	8J	265	739	875	1929	300	44	8
245/45ZR19	98	W	8J	243	703	750	1653	300	44	7.4
215/50R18	92	V	7J	226	673	630	1389	300	44	7.4
225/45ZR19	92	W	7 1/2J	225	685	630	1389	300	44	7.4
225/50ZR18	95	W	7J	233	683	690	1521	300	44	7.4
255/35ZR19	92	W	9J	260	661	630	1389	300	44	7.4
255/45ZR18	99	W	8 1/2J	255	687	775	1709	300	44	7.4
255/40ZR19	96	W	9J	260	687	710	1565	300	44	7.4
235/35ZR19	87	W	8 1/2J	241	647	545	1201	300	44	7.4
275/40ZR20	102	W	9 1/2J	278	728	850	1874	300	44	7.4
275/45ZR20	106	W	9J	273	756	950	2094	300	44	7.4
235/50R18	97	V	7 1/2J	245	693	730	1609	300	44	7.4
245/40ZR19	94	W	8 1/2J	248	679	670	1477	300	44	7.4
225/60R18	100	V	6 1/2J	228	727	800	1764	300	44	7.8
235/50ZR19	99	W	7 1/2J	245	719	775	1709	300	44	7.8
255/55ZR19	107	W	8 1/2J	265	763	975	2149	300	44	7.8
235/55ZR20	102	W	7 1/2J	245	766	850	1874	300	44	7.8
255/50ZR20	109XL	W	8J	265	764	1030	2271	300	44	7.8
255/55ZR20	110XL	W	8J	265	788	1060	2337	340	44	7.4
255/45ZR20	101	W	8 1/2J	255	738	825	1819	300	44	7.8
275/45ZR19	104	W	9J	273	731	900	1984	300	44	7.8
275/40ZR19	101	W	9 1/2J	278	703	825	1819	300	44	7.8
275/35ZR19	96	W	9 1/2J	278	675	710	1565	300	44	7.8
265/50ZR19	106	W	8 1/2J	277	749	950	2094	300	44	7.8
255/45ZR19	100	W	8 1/2J	255	713	800	1764	300	44	7.8
235/45ZR19	95	W	8J	236	695	690	1521	300	44	7.8
235/40ZR19	92	W	8 1/2J	241	671	630	1389	300	44	7.8
255/40ZR18	95	W	9J	260	661	690	1521	300	44	7.4
245/50ZR18	100	W	7 1/2J	253	703	800	1764	300	44	7.4