



SL288

规格 SIZE	花纹深度 T.D.	断面宽 S.W.	外直径 O.D.	最大负荷 MAX LOAD	气压 PRESSURE	标准轮辋 RIM
AT25×8-12-6PR	15mm	200mm	635mm	340LBS	7PSI	6.5AT
AT25×10-12-6PR	16mm	215mm	645mm	420LBS	7PSI	8.0AT
AT26×9-12-6PR	16mm	215mm	665mm	410LBS	7PSI	7.0AT
AT26×11-12-6PR	16mm	225mm	668mm	480LBS	7PSI	8.5AT
AT21×7-10-6PR	15mm	175mm	530mm	235LBS	7PSI	5.5AT
AT22×7-10-6PR	15mm	175mm	558mm	255LBS	7PSI	5.5AT
AT22×10-10-6PR	15mm	252mm	558mm	355LBS	7PSI	8.0AT



SL501

规格 SIZE	花纹深度 T.D.	断面宽 S.W.	外直径 O.D.	最大负荷 MAX LOAD	气压 PRESSURE	标准轮辋 RIM
AT27x9-14-6PR	20.5mm	229mm	684mm	849LBS	12PSI	7.0AT
AT27x11-14-6PR	20.5mm	250mm	704mm	1041LBS	12PSI	8.5AT
AT30x12-14-6PR	20mm	304mm	762mm	1433LBS	12PSI	10.0AT



SL506

规格 SIZE	花纹深度 T.D.	断面宽 S.W.	外直径 O.D.	最大负荷 MAX LOAD	气压 PRESSURE	标准轮辋 RIM
AT25x8-12-6PR	15mm	203mm	635mm	340LBS	7PSI	6.5AT
AT25x10-12-6PR	15mm	254mm	635mm	420LBS	7PSI	8.0AT
AT27x9-14-6PR	15mm	229mm	684mm	849LBS	12PSI	7.0AT
AT27x11-14-6PR	15mm	250mm	704mm	1041LBS	12PSI	8.5AT



SL306

规格 SIZE	花纹深度 T.D.	断面宽 S.W.	外直径 O.D.	最大负荷 MAX LOAD	气压 PRESSURE	标准轮辋 RIM
AT26x9-14-6PR	19mm	228mm	670mm	801LBS	18PSI	7.0AT
AT26x11-14-6PR	19mm	253mm	680mm	966LBS	18PSI	8.5AT
AT27x9-12-6PR	20mm	240mm	690mm	440LBS	7PSI	7.0AT
AT27x11-12-6PR	20mm	250mm	686mm	495LBS	7PSI	8.5AT
AT28x10-12-6PR	20mm	250mm	700mm	600LBS	7PSI	8.0AT
AT28x12-12-6PR	20mm	261mm	721mm	710LBS	7PSI	9.5AT
AT27x9-14-6PR	20mm	229mm	684mm	849LBS	18PSI	7.0AT
AT27x11-14-6PR	20mm	250mm	704mm	1041LBS	18PSI	8.5AT
AT28x10-14-6PR	20mm	223mm	714mm	1002LBS	18PSI	8.0AT
AT30x10-14-6PR	20mm	237mm	767mm	1134LBS	18PSI	8.0AT



SL366

规格 SIZE	花纹深度 T.D.	断面宽 S.W.	外直径 O.D.	最大负荷 MAX LOAD	气压 PRESSURE	标准轮辋 RIM
19x7-8-4PR	6.5mm	175mm	480mm	220LBS	10PSI	5.5AT



SL316

规格 SIZE	花纹深度 T.D.	断面宽 S.W.	外直径 O.D.	最大负荷 MAX LOAD	气压 PRESSURE	标准轮辋 RIM
AT27x9-12-6PR	27mm	215mm	690mm	440LBS	7PSI	7.0AT
AT27x11-12-6PR	31mm	241mm	682mm	495LBS	7PSI	8.5AT
AT28x10-14-6PR	30mm	223mm	714mm	1002LBS	18PSI	8.0AT
AT28x12-14-6PR	30mm	250mm	710mm	1100LBS	18PSI	9.5AT



SL308

规格 SIZE	花纹深度 T.D.	断面宽 S.W.	外直径 O.D.	最大负荷 MAX LOAD	气压 PRESSURE	标准轮辋 RIM
AT27x9-12-6PR	25mm	227mm	685mm	440LBS	7PSI	7.0AT
AT27x11-12-6PR	25mm	247mm	685mm	495LBS	7PSI	8.5AT
AT28x10-14-6PR	30mm	218mm	712mm	1002LBS	18PSI	8.0AT
AT28x12-14-6PR	30mm	255mm	723mm	1100LBS	18PSI	9.5AT



MX618

规格 SIZE	花纹深度 T.D.	断面宽 S.W.	外直径 O.D.	最大负荷 MAX LOAD	气压 PRESSURE	标准轮辋 RIM
AT30x10-14-6PR	38mm	237mm	767mm	1134LBS	18PSI	8.0AT
AT31x10-15-6PR	38mm	230mm	787mm	1185LBS	18PSI	8.0AT
AT32x10-17-6PR	38mm	224mm	814mm	1209LBS	18PSI	8.0AT
AT34x10-17-6PR	38mm	238mm	860mm	1365LBS	18PSI	8.0AT



SL386

规格 SIZE	花纹深度 T.D.	断面宽 S.W.	外直径 O.D.	最大负荷 MAX LOAD	气压 PRESSURE	标准轮辋 RIM
20×10-9-6PR	12mm	252mm	505mm	300LBS	7PSI	8.0AT



SL601

规格 SIZE	外直径 O.D.	断面宽 S.W.	花纹深度 T.D.	轮辋 RIM	气压 PRESSURE	最大负荷 MAXLOAD	负荷指数 & 速度级别
24X8-12	609mm	203mm	8mm	6.0AT	50KPa	308LBS	40J
24X10-12	609mm	254mm	8mm	8.0AT	50KPa	396LBS	48J



SL606

规格 SIZE	外直径 O.D.	断面宽 S.W.	花纹深度 T.D.	轮辋 RIM	气压 PRESSURE	最大负荷 MAXLOAD	负荷指数 & 速度级别
29X9-14	736mm	228mm	12mm	7.0AT	83kpa	480LBS	55J
29X11-14	736mm	279mm	12mm	9.0AT	83kpa	552LBS	60J



SAND TIRE 沙漠胎

E-1

规格 SIZE	层级 P.R.	标准轮辋 RIM	最大负荷 MAX LOAD (kg)	相对气压 PRESSURE (kpa)	外直径 O.D. (mm)	断面宽 S.W. (mm)
16.00-20	16	10.00W	8km/h 5450	245	1370	420
14.00-20	18	10.00W	65km/h 3150	245	1200	375
9.00-17TL	8	7J	5600	310	860	265
9.00-16TL	8	6.50H	1320	350	890	245
9.00-15	8	5.50F	8km/h 1650 65km/h 950	245	840	235

