



GTMX

TIRES & WHEELS



CATÁLOGO DE PRODUCTO
2024

INDUSTRIAL



F3

Size	PR	Rim	"Overall Diameter (mm)"	"Section Width (mm)"	"Load Capacity (kg)"	"Inflated Pressure (kPa)"	"Inflated Pressure (Psi)"	Pattern
11L-15	10	8LB	783	279	1060	360	52	F-3
11L-16	12	8LB	808	279	1250	440	64	F-3



R4

Size	PR	Rim	"Overall Diameter (mm)"	"Section Width (mm)"	"Load Capacity (kg)"	"Inflated Pressure (kPa)"	"Inflated Pressure (Psi)"	Pattern
16.9-24	12	W15L	1309	429	3250	260	38	R-4(2)
17.5L-24	12	W15L	1241	445	3000	250	36	R-4(2)
19.5L-24	12	W17	1314	495	3450	230	33	R-4(2)
21L-24	12	DW18	1378	533	3875	220	32	R-4(2)



TH801

Size	PR	Rim	"Overall Diameter (mm)"	"Section Width (mm)"	"Load Capacity (kg)"	"Inflated Pressure (kPa)"	"Inflated Pressure (Psi)"	Pattern
19.5L-24	12	W17	1314	495	3450	230	33	TH801

TH802

Size	PR	Rim	"Overall Diameter (mm)"	"Section Width (mm)"	"Load Capacity (kg)"	"Inflated Pressure (kPa)"	"Inflated Pressure (Psi)"	Pattern
19.5L-24	12	W17	1314	495	3450	230	33	TH802



R3

Size	PR	Rim	"Overall Diameter (mm)"	"Section Width (mm)"	"Load Capacity (kg)"	"Inflated Pressure (kPa)"	"Inflated Pressure (Psi)"	Pattern
23.1-26	14	DW20	1500	595	5600	230	33	R-3



G2/L2

Size	PR	Rim	"Overall Diameter (mm)"	"Section Width (mm)"	Max Load(kg)		Inflated Pressure 10km/h		Inflated Pressure 40km/h		Pattern
					10km/h	40kmh	kpa	psi	Kpa	Psi	
13.00-24	12	8.00TG	1280	335	5600	2725	450	65	300	44	G2/L2
14.00-24	16	8.00TG	1350	360	7300	3650	550	80	375	54	G2/L2
15.5-25	12	12.00/1.3	1275	395	/	2650	/	/	225	33	G2/L2
20.5-25	16	17.00/2.0	1490	520	/	4000	/	/	225	33	G2/L2
23.5-25	16	19.50/2.5	1615	595	/	4750	/	/	200	29	G2/L2



INDUSTRIAL



SKS1

Size	PR	Rim	"Overall Diameter (mm)"	"Section Width (mm)"	"Load Capacity (kg)"	"Inflated Pressure (kPa)"	"Inflated Pressure (Psi)"	Pattern
10-16.5	10	8.25	773	264	2135	520	75	SKS-1
12-16.5	12	9.75	831	307	2865	550	80	SKS-1
14-17.5	14	10.5	921	349	3875	550	80	SKS-1
15-19.5	14	11.75	1019	389	4565	485	70	SKS-1
11L-16	12	8LB	808	279	1250	440	64	SKS-1



SKS2

Size	PR	Rim	"Overall Diameter (mm)"	"Section Width (mm)"	"Load Capacity (kg)"	"Inflated Pressure (kPa)"	"Inflated Pressure (Psi)"	Pattern
10-16.5	12	8.25	795	264	2375	620	90	SKS-2
12-16.5	14	9.75	852	307	3075	620	90	SKS-2



SKS3

Size	PR	Rim	"Overall Diameter (mm)"	"Section Width (mm)"	"Load Capacity (kg)"	"Inflated Pressure (kPa)"	"Inflated Pressure (Psi)"	Pattern
10-16.5	12	8.25	815	264	2375	620	90	SKS-3
12-16.5	14	9.75	869	307	3075	620	90	SKS-3
11L-16	12	8LB	855	279	1250	440	64	SKS-3
12.5/80-18	12	9	1027	308	2625	370	54	SKS-3
14-17.5	14	10.5	962	349	3875	550	80	SKS-3

SKS4

Size	PR	Rim	"Overall Diameter (mm)"	"Section Width (mm)"	"Load Capacity (kg)"	"Inflated Pressure (kPa)"	"Inflated Pressure (Psi)"	Pattern
10-16.5	12	8.25	795	264	2375	620	90	SKS-4
12-16.5	14	9.75	852	307	3075	620	90	SKS-4



SKS5

Size	PR	Rim	"Overall Diameter (mm)"	"Section Width (mm)"	"Load Capacity (kg)"	"Inflated Pressure (kPa)"	"Inflated Pressure (Psi)"	Pattern
10-16.5	12	8.25	815	264	2375	620	90	SKS-5
12-16.5	14	9.75	869	307	3075	620	90	SKS-5
12.5/80-18	12	9	1027	308	2625	370	54	SKS-5
16.9-28	12	W15L	1410	429	3450	260	38	SKS-5



INDUSTRIAL

INDUSTRIAL



E3/L3

Size	PR	Rim	"Overall Diameter (mm)"	"Section Width (mm)"	Max Load(kg)		Inflated Pressure 10km/h			Pattern
					10km/h	40kmh	kpa	psi	Kpa	
16/70-20	18	13	1075	410	5800	3350	550	450	65	E3/L3
16/70-24	14	13	1175	410	5600	3350	450	350	51	E3/L3
15.5-25	16	12.00/1.3	1275	395	6500	3750	525	325	47	E3/L3
17.5-25	16	14.00/1.5	1350	445	7300	4250	475	300	44	E3/L3
20.5-25	20	17.00/2.0	1490	520	9500	6000	450	325	47	E3/L3
23.5-25	20	19.50/2.5	1615	595	10900	7300	375	300	44	E3/L3
14.00-24	24	10.00/2.0	1370	375	9500	5150	850	575	83	E3/L3

R1

Size	PR	Rim	"Overall Diameter (mm)"	"Section Width (mm)"	"Load Capacity (kg)"	"Inflated Pressure (kPa)"	"Inflated Pressure (Psi)"	Pattern
7.50-16	8	5.50F	810	205	770	280	41	R-1
11.2-24	10	W10	1105	285	1380	300	44	R-1
12.4-24	10	W11	1160	315	1640	290	42	R-1
13.6-24	10	W12	1210	345	1790	250	36	R-1
14.9-24	10	W13	1265	378	1990	230	33	R-1
16.9-24	10	W15L	1335	430	2230	200	29	R-1
23.1-26	12	DW20	1605	587	3610	170	25	R-1
12.4-28	8	W11	1260	315	1510	230	33	R-1
13.6-28	10	W12	1310	345	1910	250	36	R-1
14.9-28	10	W13	1365	378	2120	230	33	R-1
16.9-28	10	W15L	1435	430	2380	200	29	R-1
14.9-30	10	W13	1415	378	2190	230	33	R-1
16.9-30	12	W15L	1485	430	2730	240	35	R-1
18.4-30	12	W16L	1550	467	3180	230	33	R-1
16.9-34	10	W15L	1585	430	2605	200	29	R-1
18.4-34	12	W16L	1655	467	3375	230	33	R-1
13.6-38	10	W11	1565	345	2215	250	36	R-1
15.5-38	10	W14	1570	395	2320	230	33	R-1
16.9-38	10	W15L	1685	429	2760	200	29	R-1
18.4-38	12	W16L	1755	467	3575	230	33	R-1



AGRÍCOLA

AGRÍCOLA



MR1

Size	PR	Rim	"Overall Diameter (mm)"	"Section Width (mm)"	"Load Capacity (kg)"	"Inflated Pressure (kPa)"	"Inflated Pressure (Psi)"	Pattern
18.4-30	12	W16L	1550	467	3180	230	33	MR-1
23.1-30	14	DW20	1705	587	4200	200	29	MR-1
18.4-34	12	W16L	1655	467	3375	230	33	MR-1
20.8-34	12	W18L	1735	528	3785	200	29	MR-1
12.4-36	12	W11	1464	315	1925	330	48	MR-1
12.4-38	12	W12	1514	315	1905	310	45	MR-1
14.9-38	14	W13	1621	378	2725	320	46	MR-1
15.5-38	10	W14	1570	395	2320	230	33	MR-1
24.5-32	16	DW21	1803	622	4500	210	30	MR-1
30.5L-32	16	DW27	1819	775	5000	180	26	MR-1
20.8-42	12	W18L	1935	528	3750	190	28	MR-1



F2M (4RIB)

Size	PR	Rim	"Overall Diameter (mm)"	"Section Width (mm)"	"Load Capacity (kg)"	"Inflated Pressure (kPa)"	"Inflated Pressure (Psi)"	Pattern
10.00-16	10	W8L	910	275	1325	340	49	F-2M (4RIB)
11.00-16	10	W10L	970	315	1485	310	45	F-2M (4RIB)

F2 (3 RIB)

Size	PR	Rim	"Overall Diameter (mm)"	"Section Width (mm)"	"Load Capacity (kg)"	"Inflated Pressure (kPa)"	"Inflated Pressure (Psi)"	Pattern
7.50-16	8	5.50F	810	205	870	370	54	F-2(3RIB)
7.50-18	8	5.50F	860	205	945	370	54	F-2(3RIB)
10.00-16	10	W8L	910	275	1325	340	49	F-2(3RIB)
11.00-16	10	W10L	970	315	1485	310	45	F-2(3RIB)



1-1

Size	PR	Rim	"Overall Diameter (mm)"	"Section Width (mm)"	"Load Capacity (kg)"	"Inflated Pressure (kPa)"	"Inflated Pressure (Psi)"	Pattern
11L-15	8	W8L	775	280	1130	220	32	1-1
11L-16	12	W8L	803	279	1510	360	52	1-1
6.00-16	6	4.00E	710	158	685	275	40	1-1
7.50-16	10	5.50F	785	203	1240	400	58	1-1



AGRÍCOLA

LLANTA DE REMOLQUE Y SPECIALY



TH302 TH777

Metric Tire Size	Ply Rating	Load Range	Rim	"Overall Diameter (mm)"	"Section Width (mm)"	Max Load (kg)	"Inflated Pressure (PSI)"	Pattem
7.00-15	10	E	5.50F	750	200	1030	75	TH302
7.50-16	12	F	6.00G	850	215	1400	90	TH302
7.50-17	10	F	5.00F	843	212	1100	90	TH777

LLANTA ATV



TH100

Size	PR	Rim	Load Capacity		Inflated Pressure		Pattern
			LBS	kg	PSI	kPa	
AT25x8-12 TL	6	6.5AT	340	155	7	45	TH100
AT25x10-12 TL	6	8.0AT	420	190	7	45	TH100
AT26x9-12 TL	6	7.0AT	410	185	7	45	TH100
AT26x11-12 TL	6	9.0AT	480	218	7	45	TH100